



www.class1inc.com

Central IPC Monitor

✓16 Signals
✓32 Signals

✓48 Signals
✓64 Signals

Features

- ✓ Modular Design
- ✓ 16 to 64 Signals
- ✓ Recent Alarm History
- ✓ Transient Signal Filter
- ✓ Transient Signal Detection & Display
- ✓ Multiple Panel Capable



Specifications

Class 1 AC Series, CSA certified, modular, microprocessor controlled Central IPC Monitor to monitor and display status of Line Isolation Monitors of multiple Isolated Power Centres.

Display Panel: 16 signal module(s) to include continuous green LED SAFE indicators and continuous red LED HAZARD indicators for each Line Isolation Monitor. Base module to include user accessible SILENCE and TEST buttons, Power ON LED, and Information Code Display.

Features:

- Alarm History Recall and display
- Transient alarm trapping and display.
- 90 dBa audio alarm
- Multiple and subsequent audiovisual alarms

Backbox: Enamel painted steel backbox complete with internal, enclosed, CSA approved 120V/12V power supply and wiring harness.

Front Panel: Formed enamel painted steel providing housing for the circuit boards. Hinged mounting hardware and lanyards to allow easy installation and service.

Connections: One 16 to 22 ga. unshielded twisted pair to be connected from each LIM to the terminals in the Central IPC Monitor.

Power Requirements: One 120V 15A Emergency Power circuit.

Warranty: One year replacement warranty on complete unit; 3 year replacement warranty on circuit boards.

© 2001- 2002 Class 1 Inc. Updated: August 23, 2002